

## Standard Recovery Diode, 60A

### Features

- Glass passivated die
- Low forward voltage drop
- High surge capability
- Low leakage current
- Normal and Reverse polarity
- Metric and UNF threads available



DO-203AB (DO-5)

Maximum Ratings ( $T_J = 25^\circ\text{C}$ , unless otherwise noted)							
Parameter	Test Conditions	Symbol	1N2128A(R)	1N2129A(R)	1N2130A(R)	1N2131A(R)	Units
Repetitive peak reverse voltage		$V_{RRM}$	50	100	150	200	V
RMS reverse voltage		$V_{RMS}$	35	70	105	140	V
DC blocking voltage		$V_{DC}$	50	100	150	200	V
Continuous forward current	$T_C \leq 150^\circ\text{C}$	$I_{F(AV)}$	60	60	60	60	A
Surge non-repetitive forward current, half-sine wave	$T_C = 25^\circ\text{C}$	$I_{FSM}$	1050	1050	1050	1050	A
Maximum peak forward voltage	$I_F = 60\text{A}, T_J = 25^\circ\text{C}$	$V_F$	1.1	1.1	1.1	1.1	V
Reverse current	$T_J = 25^\circ\text{C}$	$I_R$	10	10	10	10	$\mu\text{A}$
	$T_J = 140^\circ\text{C}$		15	15	15	15	mA

Thermal & Mechanical Specifications ( $T_J = 25^\circ\text{C}$ , unless otherwise noted)						
Parameters	Symbol	1N2128A(R)	1N2129A(R)	1N2130A(R)	1N2131A(R)	Units
Thermal resistance, junction to case	$R_{th(jc)}$	0.65	0.65	0.65	0.65	$^\circ\text{C}/\text{W}$
Operating junction temperature range	$T_J$	-55 to 160	-55 to 160	-55 to 160	-55 to 160	$^\circ\text{C}$
Storage temperature	$T_{stg}$	-55 to 160	-55 to 160	-55 to 160	-55 to 160	$^\circ\text{C}$
Mounting torque, non-lubricated threads, tightening on nut	F	3.4 $\pm$ 10%				Nm
Approximate weight	W	16				g

**Package Outline****Dimensions for DO-203AB (DO-5) (in millimeters)**